



BXH20262

Adjustable Ball Mount Installation Instructions

US Patent #8, 033, 563



Adjustable Ball Mount BXH20262

2-1/2" Receiver, 6" Drop/Rise, 20,000 lbs. capacity rated
2-5/16" Pintle Hook Accessory



WARNING

Do not exceed vehicle's towing capacity or receiver hitch capacity, whichever is less.
See your Vehicle Owner's Manual to determine Vehicle Tow Rating.

BXH20262

Adjustable Ball Mount Installation Instructions

Disclaimer

The rating of the Adjustable Ball Mount is intended to represent the capability of the product and in no way reflect the ratings or capacity of the towing system it is being used with. You, the consumer or operator, are strongly advised to learn the ratings of the various components of the towing system and never exceed the limits of the lowest rated component being used.

- The 2-5/16" Pintle Hook Accessory is rated for 20,000 lbs. capacity.

Installation Instructions

1. Install DFP (dual flange platform) into the 2-1/2" receiver hitch of your vehicle and secure with the included hitch pin and clip. Always secure the hitch pin with a cotter pin unless a locking device is being used. **See Illustration A.**

2. Raise or lower the Pintle Hook Accessory to the desired height and insert the supplied pins through the holes that line up with the holes in the platform. Secure the pins with the included cotter pins. **See Illustration B.**

Note: The supplied pins are specifically engineered for the Adjustable Ball Mount. If replacement pins are needed, they must be replaced with original factory pins.

3. After adjusting ball height and securing with Adjustable Ball Mount pins, tighten the Anti-Rattle set screw tightly into the back of the Pintle Accessory to eliminate noise. **See Illustration C.**

Note: Use of set screw is not needed for safety; only to eliminate possible rattle between the DFP and the Pintle.

4. Prior to towing, check to make sure that the pins are secured into place with cotter pins.

5. Never hook up trailer safety chains to the Adjustable Ball Mount.



WARNING

Please ensure that the safety chains operate freely around the Adjustable Ball Mount and don't become entangled in the Platform or Pintle Hook Accessory.



WARNING

Use of any pin other than of original manufacture could be a serious safety hazard and will void the warranty.

BXH20262
Adjustable Ball Mount
Installation Instructions

CUSTOMER SERVICE COMMITMENT

Blue Ox® is committed to providing you with exceptional customer care throughout your lifetime with our products. Our team is here to assist you with any questions you may have regarding the performance of your product. Simply call (402) 385-3051 and you can speak with our customer care team.

Additionally, please visit our website to see which rallies our Destination America team will be attending. For a nominal fee, our service technician will service your towing system to ensure it's in proper working condition. Also, as a commitment to our customers, should you visit our factory, you can stay at our full service Blue Ox® campground at no charge along with enjoying a factory tour.

Again, thank you for being our customer and for the confidence you have shown in the performance of our products. It is because of customers like you we enjoy the success we have today.



© 2013 Blue Ox
One Mill Road, Industrial Park
Pender, Nebraska 68047
Phone: (402) 385-3051
Fax: (402) 385-3360
www.blueox.com